

PRODUCT SAFETY INFORMATION SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

TRADE NAME: RT/Duroid® 6002 Laminates

CHEMICAL FAMILY: Polytetrafluoroethylene Composite

HMIS RATING: H 1 F 1 R 0

USE OF ARTICLE Printed Circuit Boards

DATE ISSUED: February 19, 2018

COMPANY/UNDERTAKING Rogers Corporation

IDENTIFICATION: 100 South Roosevelt Avenue

Chandler, AZ 85226-3415 Phone: 001-480-961-1382 Fax: 001-480-961-4533

Email: msdsinfo@rogerscorporation.com

2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE NE

MATERIAL:

LABELING REQUIREMENTS: NE

EFFECTS OF OVEREXPOSURE: None anticipated with normal handling. Machining may create dust. Processing

material at temperatures exceeding decomposition temperature may release

toxic fumes.

INHALATION: Dusts may cause respiratory irritation. Exposure to copper fume or PTFE

decomposition products may cause symptoms of metal or Polymer Fume Fever. This is characterized by flu like symptoms (fever, chills, muscle aches) that last

about 24 hours.

EYE CONTACT:

Dust may cause mechanical irritation.

SKIN CONTACT:

Dust may cause mechanical irritation.

INGESTION: None known.

CHRONIC: IARC has listed Microfiber Glass as Group 2B (possibly carcinogenic to

humans).

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is produced as an "article" as defined in 20 CFR 1910.1200 and REGULATION (EC) N° 1907/2006 is therefore exempt from the Hazard Communication Standard and REACH. Since this material does not release and will not result in exposure to a hazardous chemical under normal conditions of use, no Safety Data Sheet is required.

Chemical Name	CAS No.	EINECS	<u>%</u>	OSHA PEL	ACGIH	EU Classification
Microfiber Glass (Encapsulated in a Polymer Matrix)	65997-17-3	<u>/ELINCS</u> 266-046-0	Varies	5 mg/m ³ (Resp. Dust)	<u>TLV</u> 1 f/cc	Not Classified Under 67/548/EEC
Fused Silica	60676-86-0	262-373-8	Varies	5 mg/m ³ (Resp. Dust)	3 mg/m ³ (Resp. Dust)	Not Classified Under 67/548/EEC
Copper	7440-50-8	231-159-6	Varies	1 mg/m ³ (dust & mist)	1 mg/m ³ (dust & mist)	Not Classified Under 67/548/EEC

Aluminum

INGESTION:

7429-90-5

231-072-3

5 mg/m³ Varies (Resp. Dust)

 1 mg/m^3 (Resp. Dust)

Not Classified Under 67/548/EEC (only Al powder is Classified)

FIRST-AID MEASURES 4.

INHALATION: (Dust & Fume) Remove to fresh air. Obtain medical attention if symptoms

persist.

EYE CONTACT: (Dust) Flush immediately with large amounts of water for 15 to 20 minutes. Do

not rub eyes. Obtain medical attention if symptoms persist.

(Dust) Remove contaminated clothing and flush area with water for 15 to 20 SKIN CONTACT:

> minutes. Obtain medical attention if symptoms persist. (Dust) Not a likely route of entry – obtain medical attention.

5. FIRE-FIGHTING MEASURES

NE °C (°F) Flammable Limits: NE FLASH POINT:

AUTOIGNITION TEMPERATURE: NE °C (°F)

 $\begin{array}{cccc} \text{Water Spray} & \underline{X} & \text{Foam} & \underline{X} & \text{CO}_2 \\ \text{Dry Chemical} & \overline{X} & \text{Other} - \end{array}$ **EXTINGUISHING MEDIA:**

SPECIAL FIRE FIGHTING

PROCEDURES:

Decomposition in a fire may produce toxic fumes. Firefighters should be

equipped with self-contained breathing apparatus and turnout gear.

UNUSUAL FIRE AND EXPLOSION

HAZARDS:

None known.

6. **ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS: In case of fire toxic fumes are emitted. Wear suitable protective equipment. Do

not breathe dust. Eliminate sources of ignition. Avoid contact with skin and

ENVIRONMENTAL PRECAUTIONS:

CLEANING METHODS:

Prevent from entering sewer system, surface water or soil.

Sweep or shovel into appropriate container for disposal. Avoid creation of

nuisance dust.

HANDLING AND STORAGE 7.

HANDLING: Wear suitable protective equipment, refer to Section 8.

STORAGE: Keep in a cool, well-ventilated area.

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

RESPIRATORY PROTECTION: None needed under normal conditions. If mechanical ventilation is absent or

> inadequate to maintain exposure levels below those listed in Section 2, a respirator meeting NIOSH requirements should be used. A qualified individual

should evaluate each situation.

VENTILATION

LOCAL: Recommended for all industrial operations. **GENERAL:** Recommended for all industrial operations.

PERSONAL PROTECTION

HAND: Cut resistant gloves.

EYE: Safety glasses with side-shields are recommended in all industrial operations SKIN: None Required

OTHER: Safety shower/eyewash in the area. Do not smoke or keep smoking materials

in areas where material is machined or excessive dusting occurs. Wash

thoroughly before eating or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Gray or White board Clad with Copper, Aluminum, or Brass

 ODOR:
 None

 PHYSICAL STATE:
 Solid

 BOILING POINT:
 NA °C (°F)

 MELTING POINT:
 NE °C (°F)

 FREEZING POINT:
 NA °C (°F)

 FLASH POINT:
 NE °C (°F)

WATER SOLUBILITY: NE VAPOR DENSITY: NA VAPOR PRESSURE: NA

SPECIFIC GRAVITY: NE (Water = 1)

PARTITION COEFFICIENT: NA
EVAPORATION RATE: NA
RELATIVE DENSITY: NA
VISCOSITY: NA

AUTO-IGNITION TEMPERATURE: NE °C (°F)
DECOMPOSITION TEMPERATURE: NE °C (°F)
PH: NA

FLAMMABILITY: NE

10. STABILITY AND REACTIVITY

STABILITY Stable

CONDITIONS TO AVOID: PTFE begins to decompose very slowly above 500°F. Decomposition

increases rapidly above 750°F and processing at these temperatures for

prolonged periods of time is not recommended.

MATERIALS TO AVOID: NE

HAZARDOUS POLYMERIZATION: Does not occur

HAZARDOUS DECOMPOSITION

PRODUCTS:

Tetrafluoroethylene (above 800°F)

Hexafluoropropylene (above 825°F)

Perfluoroisobutylene (above 885°F)

Perfluoroisobutylene (above 885°F) Carbonyl Fluoride (above 930°F)

11. TOXICOLOGICAL INFORMATION

CARCINOGENIC STATUS: IARC has listed Microfiber Glass as Group 2B (possibly carcinogenic to

humans).

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NE

13. DISPOSAL CONSIDERATION

PHYSICAL/CHEMICAL PROPERTIES AFFECTING DISPOSAL:

ENVIRONMENTAL TOXICITY DATA: NE

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable federal, state, provincial, and local

laws and regulations.

3 of 4

14. TRANSPORT INFORMATION

UN NUMBER:
UN PROPER SHIPPING NAME:
HAZARD CLASS (ES):
PACKING GROUP:
Not Regulated
Not Regulated
Not Regulated

ENVIRONMENTAL HAZARDS: NE

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS:

Canadian (DSL/NDSL):

Australian (ACIS):

Korea (KECI):

Japan (ENCS, MITI):

China (IECSC)

Article – exempt.

EU Directive 2011/65/EC (RoHS): Does not contain any intentionally added substances mentioned by the RoHS

directive.

European:

Symbol Not classified according to directive 1999/45/EC & 2001/60/EC (dangerous

preparations).

R-Phase(s):

S-Phase(s):

NA

NA

TSCA All materials are listed or exempt from TSCA listing.

(Toxic Substances Control Act):

CERCLA NA

(Comprehensive Emergency Response,

Compensation, and Liability Act):

SARA TITLE III NA

(Superfund Amendments and

Reauthorization Act):

311/312 HAZARD CATEGORIES: None

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS #CHEMICAL NAMEPERCENT BY WEIGHT7429-90-5AluminumVaries7440-50-4CopperVaries

16. OTHER INFORMATION

NA = Not Applicable FILE: 99041-RT Duroid 6002 Laminates-02192018

NE = Not Established

NC = Not Classified PREPARED BY: Curtis Kempton
Date Prepared: 03/13/2014 REVIEWED BY: Michal Werbecki
REVIEWED BY: EHS Department

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF.

ROGERS CORPORATION ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.