

DeWAL® DW132-6

DeWAL® DW132-6 is a PTFE impregnated glass fabric. The PTFE provides a smooth anti-stick surface while the glass fabric provides strength and dimensional stability. This product is a "non-adhesive" product.

Features & Benefits:

- Good strength
- High temperature resistance
- Dimensional stability
- Non-stick surface

Applications:

- Covers for food preparation tables
- Heat sealing bars

PROPERTY	TEST METHOD	DATA RANGE	TYPICAL VALUE*
PHYSICAL			
Backing Material			PTFE Glass Cloth
Backing Thickness, mm (inches)		0.14 – 0.17 (0.0055 – 0.0067)	
Adhesive System			No Adhesive
Adhesive Thickness, mm (inches)			
PTFE Impregnation, kg/m ² (lb/yd ²)		0.30 – 0.35 (0.55 - 0.65)	0.325 (0.60)
Maximum Operating Temperature, C° (F°)		260 (500)

PRODUCT DIMENSIONS	METRIC	ENGLISH	
Width mm, inches	6.35 – 965	0.25 – 38	
Core Diameter mm, inches	76	3	
Roll Length m, yards	33	36	

*Typical values shown are from testing at date of manufacture and should not be used for specification limits.

- Additional technical information and product specifications are available upon request.

- Shelf life is 1 year from the date of manufacture with storage conditions of 21°C (70°F) and 50% RH.

- All metric conversions are approximate.



The information contained in this Data Sheet is intended to assist you in designing with Rogers' Elastomeric Material Solutions. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers DeWAL products for each application. The Rogers logo, DeWAL logo and DeWAL are trademarks of Rogers Corporation or one of its subsidiaries. © 2019, 2020 Rogers Corporation. All rights reserved. 0320-PDF • Publication #175-134